Product Specification 6525-08

Taconic 6525-08 is a plasma spray masking tape constructed from silicone coated fiberglass complete with silicone adhesive. The tape is a reliable maskant to protect against heat and abrasion associated with surface prep blasting, electric arc spray, combustion flame spray, and plasma spray coatings. The tape is designed to release cleanly from metal surfaces leaving no adhesive residue. This tape comes with a yellow dimpled PVC release liner. Maximum width is 96,52cm wide.

Product Properties	Units	Value	Tolerance	Test Method
Adhesive Type		**Silicone**		
Substrate Type		**E-GLASS**		
Total Weight of Substrate	g/m2	**N/A**		ISO2286-2
% Coating of Substrate		**N/A**		
Substrate Thickness	micron	**253**		
Adhesive Thickness		**75**		ISO2286-3
Total Product Thickness	micron	**328**		
Adhesive Strength	N/25,4mm	**11**	Typical	ISO8510-2
		6	Minimum	
Operating Temperature	°Celsius	**-73° to +260°**		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.

QUALITY ISO 9001:2015 NSAI Certified
ENVIRONMENT ISO 14001:2015 NSAI Certified

Please contact us for samples or a quotation

TÜV SÜD ISO 9001

Taconic International Ltd
Ireland
www.taconic-ipd.com
info@taconic-ipd.com

Taconic France
France
www.taconic-ipd.fr
info@taconic-ipd.fr

Taconic International Ltd
Germany
www.taconic.de
info@taconic.de

Wildcat Taconic
United Kingdom
www.taconic-ipd.com
info@wildcat-taconic.com

Taconic SP z.o.o
Poland
www.taconic-ipd.pl
biuro@4taconic.com

For queries in North America please visit www.4taconic.com or email info@4taconic.com

REACH COMPLIANCE RoHS

Rev: 06/22 - 001